

1. (currently amended) A method for determining formation fluid pressure in earth formation surrounding a borehole, the borehole defining a borehole wall, the borehole wall covered with mud cake forming a mud cake seal, the method comprising:
 - providing a tool defining a probe and a variable-volume pretest cavity fluid-coupled to the probe;
 - pressing a the probe into contact with the mud cake ~~and formation at the borehole wall;~~
 - expanding the volume of ~~a variable-volume pretest~~ the cavity ~~that is in fluid communication with the probe in sufficient amount to produce a break in the mud cake seal during a draw-down period to break a mud cake seal at the probe;~~
 - ~~terminating expanding the volume of the cavity on~~ holding constant the volume of the cavity immediately after detecting the occurrence of a the break in the mud cake seal, for a sufficient build-up period to establish pressure equilibrium between cavity fluid and formation fluid;
 - ~~allowing a build-up period to establish pressure equilibrium between tool fluid and formation fluid;~~
 - measuring tool pressure in the cavity; and
 - setting formation fluid pressure equal to tool measured pressure ~~at pressure equilibrium.~~
2. (currently amended) A method according to claim 1, wherein detecting the a break in the mud cake seal includes measuring ~~tool~~ cavity pressure and detecting an abrupt change associated with ~~tool~~ cavity pressure.
3. (currently amended) A method according to claim 2, wherein detecting the abrupt change includes using a finite moving average (FMA) algorithm on a function of ~~tool~~ cavity pressure.

4. (currently amended) A method according to claim 3, wherein the function of ~~tool~~ cavity pressure includes ~~tool~~ cavity pressure.
5. (currently amended) A method according to claim 3, wherein the function of ~~tool~~ cavity pressure includes a first derivative of ~~tool~~ cavity pressure.
6. (currently amended) A method according to claim 3, wherein the function of tool pressure includes a second derivative of ~~tool~~ cavity pressure.
7. (currently amended) A method according to claim 1, wherein detecting the a break in the mud cake seal includes detecting a difference between a measured ~~tool~~ cavity pressure and a corresponding ~~tool~~ cavity pressure from a reference ~~tool~~ cavity pressure profile.
8. (currently amended) A method according to claim 7, wherein the reference ~~tool~~ cavity pressure profile is measured in a previous drawdown with the cavity isolated from the formation.
9. (original) A method according to claim 1, further comprising:
expanding the volume of the cavity during the draw-down period at a predetermined constant rate.
10. (original) A method according to claim 9, wherein the predetermined constant rate is within the range of 3-160cc/minute.
11. (original) A method according to claim 10, wherein the predetermined constant rate is approximately 5cc/minute.

12. (currently amended) A tool for determining formation fluid pressure in earth formation surrounding a borehole, the borehole defining a borehole wall, the borehole wall covered with mud cake forming a mud cake seal, the tool comprising:
- an elongated body adapted for downhole operation;
 - a probe, extendable from the elongated body, the probe defining an inflow aperture;
 - a pretest piston pump defining a variable-volume pretest cavity coupled to the inflow aperture;
 - a) means for expanding the volume of the pretest cavity in sufficient amount to produce a break in the mud cake seal,
 - b) means for detecting an occurrence of a break in the mud cake seal, and
 - c) means for holding constant the volume of the cavity immediately after detecting the occurrence of the break in the mud cake seal, for a sufficient build-up period to establish pressure equilibrium between pretest cavity fluid and formation fluid;
 - and
 - a pressure sensor coupled to measure pressure in the pretest cavity;
 - a pretest flow line coupling the inflow aperture to the cavity;
 - ~~pressure measuring means, pressure coupled to the cavity for measuring tool~~
~~pressure; and~~
 - ~~electromechanical control means for controlling the volume of the cavity~~.
13. (original) A tool according to claim 12, wherein the control means includes an electromechanically driven roller screw planetary system.
14. (original) A tool according to claim 13, wherein the control means further includes an electrically driven gearbox coupled to drive the roller screw planetary system.

15. (original) A tool according to claim 12, wherein the control means includes downhole programmable control electronics coupled to control the electromechanical control means.
16. (original) A tool according to claim 12, wherein the tool includes a constant-volume flow line.
17. (original) A tool according to claim 16, wherein the constant-volume flow line includes a dedicated probe.
18. (original) A tool according to claim 16, wherein the constant-volume flow line includes a flexible conduit.
19. (original) A tool according to claim 16, wherein the constant-volume flow line has a volume in the range 20 - 120cc.
20. (original) A tool according to claim 12, wherein the probe is located between the pressure measuring means and the variable-volume pretest cavity.
21. (original) A tool according to claim 12, further comprising a sample line coupled to the cavity, and an isolation valve located between the cavity and the sample line.
22. (original) A tool according to claim 12, further comprising an isolation valve located between the cavity and the formation fluid inflow aperture.
23. (original) A tool according to claim 12, wherein said electromechanical control means includes means for terminating expansion of the volume of the cavity on detecting a break in a mud cake seal.